



## Professional Network Label Printer Range

Print durable labels from your PC, Mac, smartphone or tablet using wireless or wired network connectivity.

- Create durable labels up to 36mm in width
- High speed and high resolution printing
- Wired network\* & Wi-Fi to print labels from several devices at once, including tablets/smartphones
- Advanced cutter with easy label peel function
- Include images, barcodes and frames on your labels
- Connect to data contained in spreadsheets to batch print many labels at once
- Software development kits available for Windows, iOS and Android devices
- Range of optional accessories to customise the printer to your needs

\*PT-P950NW only



## Specifications

### Label printing

Prints labels up to 36mm in width  
Maximum print height of 32mm for near edge-to-edge printing  
360dpi print resolution for crisp, legible text, images and barcodes  
Fast print speed of 60mm/second  
Built-in automatic label cutter with easy-peel function  
Minimum label length: 4mm | Maximum label length: 1 meter  
Print up to 17 lines per label  
Number of copies: 1-999  
Connectivity: Wired

USB: Windows®(USB1.1, 2.0, 3.0 protocol) | Mac (USB 1.0, 2.0 protocol)  
Network: 10 Base-T/100 Base-TX (PT-P950NW only)  
Serial: RS-232C (for printing with ESC/P commands only. Requires optional serial adapter)  
Connectivity: Wireless

Wireless Direct: IEEE802.11n | Ad-Hoc mode: IEEE802.11b | Infrastructure mode: IEEE802.11b/g/n | WPS 2.0  
Connectivity: Bluetooth (optional accessory for PT-P950NW)

Bluetooth 2.1+EDR | Profiles: SPP, OPP

### Printer emulations/printer modes

P-touch Raster | ESC/P | P-touch Template

### Label creation (PC/Mac)

Uses P-touch Editor professional label design software  
Link to data stored in Microsoft® Excel® (Windows®) and .csv (Mac) files, to merge onto your labels  
Choose any of the fonts installed on your PC/Mac to fully customise your label  
Supports popular image formats (.bmp, .dib, .jpg, .tif, .ico, .wmf)  
Special cable labelling wizard to easily create labels for cables, patch panels, faceplates and switches  
Use the date/time stamp to automatically include current or future date/time on your labels  
Barcode protocols supported:

1D: CODE39, CODE128, ITF 2/5, EAN13, EAN8, UPC-A, UPC-E, CODABAR, GS1-128 (UCC/EAN128)  
2D: QR Code, PDF417, Data Matrix, Aztec Code, RSS-14 (Standard, Truncated, Stacked, StackedOmni), RSS-Limited, RSS Expanded (Standard, Stacked)

### Dimensions and weights

118mm (w) x 192mm (d) x 146mm (h) | 1.48kg (PT-P900W) / 1.51kg (PT-P950NW)

### Supplied with printer

36mm black on white laminated label cassette (8m)  
AC adapter  
USB cable  
User guide

### Tape types supported

TZe tape cassettes: 3.5mm-36mm  
HSe heat-shrink tube: 5.8mm-23.6mm

### System Requirements

Operating Systems: Microsoft® Windows Vista® | Microsoft® Windows® 7 | Microsoft® Windows® 8 | Microsoft® Windows® 8.1  
Microsoft® Windows® 10 | Microsoft® Windows Server® 2008 | Microsoft® Windows Server® 2008 R2 | Microsoft® Windows Server® 2012  
Microsoft® Windows Server® 2012 R2 | Mac OS X 10.9.5/10.10.x/10.11.x  
Hard disk space: Windows®: More than 70MB | Mac: More than 500MB  
Microsoft, Windows, Windows Server and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Apple, Mac, Mac OS, iPhone, iPad and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.  
Microsoft® Word 2007/2010/2013/2016 | Microsoft® Excel® 2007/2010/2013/2016 | Microsoft® Outlook® 2007/2010/2013/2016  
System memory: As per operating system requirements  
Microsoft® Office® support for P-touch add-in:



Scan Here



bit.ly/bro-id



### Brother iShop

Get this app for free and enjoy all benefits!  
Available on Apple Store and Google Play.

Contact:

