

## Print On-The-Go: Maximize productivity with the Ultra-Compact, Ultra-Light

# LK-P25

2-Inch Mobile Receipt Printer



### KEY FEATURES



#### Ultra portable Ultra flexible

- 5-Pin micro -USB : Compatible with smart phone, tablet and other peripherals.
- Easy pairing process using NFC Tag.
- Long battery life : 3.7V / 2,600mAh. Rechargeable Li-ion battery.
- Print entire shift : Print over 160 meters via Bluetooth with fully charged battery.



#### Seamless communication

- Simultaneously connect to multiple peripherals via Bluetooth 4.2 classic and Low Energy (BLE).
- Compatible with Android,iOS and Windows operating systems.



#### Ultra-compact design

- Ultra Compact and Lightweight : 0.19kg including battery  
79x44.4x103.2 mm / 3.1x1.7x4 inch
- Drop rating :  
5ft/1.5m (unit only) to concrete  
6ft/1.8m with case to concrete
- Sturdy belt clip for comfortable fit.



# LK-P25 2-Inch Mobile Receipt Printer

## SPECIFICATIONS

### PRINTER CHARACTERISTICS

**Print Method**

Direct thermal

**Print Speed**

Up to 2.3ips (60mm/sec)

**Print Width**

Up to 1.8" (48mm)

**Resolution**

203 dpi (8dots/mm)

**Memory**

256KB SRAM, Flash

**Battery Voltage / Capacity**

3.7V / 2600mAh.

Rechargeable Li-ion battery

**Battery Charge Time**

Adaptor : Max. 3.4Hrs

USB : Max. 5.7Hrs

**Standby Time**

79Hrs

**Sensor**

Paper end, Cover open,

Black mark

**Reliability**

TPH life : 50km

### INTERFACE

**Standard**

USB,

Bluetooth 4.2 classic

and Low Energy (BLE)

### ACCESSORIES

**Standard**

Charger(USB Cable), Battery Pack,

Thermal Roll Paper,

Belt Clip & Battery Cover

**Option**

Leather Case

### MEDIA CHARACTERISTICS

**Media Type**

Thermal paper

**Media Width**

2.2" (58mm)

**Media Core Diameter**

0.4" (12.5mm)

**Media Roll Diameter**

1.5" (40mm)

**Thickness**

0.06mm

### OPERATING CHARACTERISTICS

**Operating Temperature**

14 ~ 122°F(-10 ~ 50°C)

**Operating Humidity**

10 ~ 80%

**Storage Temperature**

-4 ~ 140°F(-20 ~ 60°C)

**Storage Humidity**

10 ~ 90%

**Drop Rating**

5ft/1.5m (unit only) to concrete

6ft/1.8m with case to concrete

### AGENCY APPROVALS

KC, CE, FCC, UL/cUL, Mfi

### PHISICAL CHARACTERISTICS

**Dimension (W x D x H)**

3.1"×1.74"×4.06" (79×44.4×103.2mm)

**Weight (Kg)**

0.4lb(0.9kg, Battery Incl.)

### SOFTWARE

**Emulation**

ESC/POS

**Driver**

Windows Driver(10, 2012, 8, 7, 2008, VISTA,

2003, XP, 32bit & 64bit), Window CE &

Mobile Driver & SDK (CE 4.2~, Mobile 5.0~),

Linux Driver, Mac Driver,

OPOS Driver, JavaPOS Driver

**SDK**

iOS, Android(2.1~), Windows,

Linux, Blackberry, Symbian

### BARCODE

**1D**

UPC-A, UPC-E, EAN-8, Code39, Code93, ITF,

Codabar, EAN-13, Code128

**2D**

QR, PDF417, Maxicode, Datamatrix

### FONT / GRAPHICS

**Character Size**

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

**Characters per Line (CPL)**

Font A(12x24): 32cpl,

Font B(9x17): 42cpl,

Chinese / Korean / Japanese: 16cpl

**Character Set**

95 Alphanumeric,

14 International,

128 x 18 Graphic



BARCODE



NFC



COMPACT  
DESIGN



58mm  
PAPER WIDTH



BLUETOOTH



1.8M DROP



LIGHT  
WEIGHT

**Republic of Korea [Head Office]**

28-6, Gajangsaneopdong-ro,  
Osan-si, Gyeonggi-do, 18103,  
Republic of Korea

T. +82-31-8077-5000

F. +82-31-624-5310

E. sales@miniprinter.com

**México**

Paseo de la Reforma No. 265 Piso 2.  
Oficina SBC. Col. Cuauhtémoc,  
C.P. 06500 Ciudad de Mexico

T. +52-1-55-3232-9543

E. sales@miniprinter.com

**North America**

20280 S. Vermont Ave. STE 200,  
Torrance, CA 90502, USA

T. +1-310-561-8030

E. sales@miniprinter.com